



ELESA original design CFTX.



Form SH

Form EH



Bohrungen für  
Senkschraube  
DIN 7991

Bohrungen für  
Zylinderschrauben DIN 912  
Sechskantschraube ISO 4014



1

2

3

l <sub>1</sub>		l <sub>2</sub>		d <sub>1</sub>		d <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> -0,5	h <sub>5</sub>	l <sub>3</sub>	m <sub>1</sub> ±0,25	m <sub>2</sub> ±0,25	sw
Nennmaß	Istmaß	Nennmaß	Istmaß												
40	38,5	40	39,5	4,5	3	13	9	4,5	4	18	16,5	25	25	7	
49	49	49	49,5	5,5	4	16,5	11,5	5	6	23	21	31	30,5	8,5	
49	49	49	49,5	6,5*	4	16,5	11,5	-	6	23	21	31	30,5	10	
65	64	65	65	6,5	5	21,5	15	9	7,5	30	27,5	40	40	10	

\* nur in Form EH lieferbar

## Ausführung

- Kunststoff (Polyamid PA)
  - schwarz, matt
  - temperaturbeständig bis 80 °C
- Stift  
Kunststoff (Polyacetal POM)
- Angaben zur Belastbarkeit → Seite 1851
- Kunststoff-Eigenschaften → Seite 1876
- RoHS

## Hinweis

siehe auch...

- Zusammenstellung der Scharniere-Bauarten → Seite 1152 ff.

Bestellbeispiel

1	l <sub>1</sub>
2	l <sub>2</sub>
3	d <sub>1</sub>
4	Form

**GN 151.5-49-49-5,5-SH**

